

## Special Glossmeter

**B**iuged Instruments also manufacture some special glossmeters which are used in other fields. All these glossmeters have the same perfect performance as our normal glossmeter. And its technical parameters are compatible to international standard such as ISO2813, ASTM D523, DIN67530 etc.



Products	Glossmeter (for plastic, film)	Glossmeter (for paper making)	Glossmeter (for metal)	Glossmeter (for stone)	Glossmeter (small orifice)
Ordering information	BGD 517/1	BGD 517/2	BGD 517/3	BGD 517/4	BGD 518
Apply for	Ceramic, Enmal, Plastic	Paper making	Metal, electroplate, glass or with high gloss surface	Marble, granite, terrazzo etc.	Curve or small area thing
Incidence Angle	45°	75°	60°	60°	60°
Reading Range	0 ~ 199.90 GU	0 ~ 199.90 GU	0 ~ 1999 GU	0 ~ 199 GU	0 ~ 199.90 GU
Facula size	10 × 14mm	8 × 20mm	10 × 20mm	10 × 20mm	2 × 2mm
Resolutio	0.1 GU	0.1 GU	1 GU	1 GU	0.1 GU
Accuracy	± 1.2 GU	± 1.2 GU	± 1.2 GU	± 2 GU	± 1.2 GU
Stability	± 0.4 GU	± 0.4 GU	± 0.4 GU	± 1 GU	± 0.4 GU