

Water/Oil Bath Kettle

Provided to colleges, industrial and mining enterprises and scientific research departments for precise constant temperature and auxiliary heating.

Features

- ◆ Interior of bath is made of stainless steel and the center lids can be removable discretionarily.
- ◆ High precision microprocessor temperature controller ensures a precise and reliable temperature control.
- ◆ Audible and visible tracking alarm indicates over-temperature, which provide samples reliable protection.



Water Bath



Oil Bath

★ Ordering Information

Ordering Information → Technical Item ↓	Water Bath (with removable center lids)				Oil Bath	
	BGD 830	BGD 831	BGD 832	BGD 833	BGD 839	BGD 840
Electrical Requirements	220V 50HZ				220V 50HZ	
Input Power	500W	1000W	1500W	2000W	1000W	2000W
Temperature Range	From ambient+5 to 99°C				From ambient+5 to 200°C	
Temperature Stability	± 0.5°C				± 0.5°C	
Tracking Alarm	± 0.2°C				± 0.2°C	
Chamber Capacity	4.9L	9.9L	14.8L	19.8L	12 L	20 L
Interior Dimension (mm) W × D × H	150 × 300 × 110	300 × 300 × 110	450 × 300 × 110	600 × 300 × 110	250 × 250 × 200	400 × 250 × 200
Timing Range	1~999min				1~999min	
Note	Two holes	Double columns four holes	Double columns six holes	Double columns eight holes	---	---