

Cone-and-plate Viscometer

Paints or inks often are in different shear rates status from manufacturing to application. As a typical Non-newtonian fluid, paints or inks always show different viscosity characteristics at different shear rates.

Generally speaking, paints are in a low shear rate state when it is stored, transported, levelling and sagging. But they are in the medium shear rate when being pumped, dipped and mixed at a low speed. And at high-speed dispersion, roll, spray and brush coating, they are in a high shear state, and the shear rate is generally $9000S^{-1}$ to $12000S^{-1}$. Therefore, understanding the rheological characteristics of paints or inks at such high shear rates requires the use of cone-plate viscometer to measure.

BGD 182 Cone-and-plate Viscometer uses a special angle conical spindle, which generates a very high shear rate on the measured sample under the high-speed drive of a stepper motor. It conforms to ISO 2884-1 « Paints and varnishes — Determination of viscosity using rotary viscometers — Part 1: Cone-and-plate viscometer operated at a high rate of shear » .

Features



Scan for video



Features

- ◆ 7-inch touch screen, menu operation, rich display content (measurement values, spindle No., speed, shear rate, etc.), simple and convenient to operate.
- ◆ Beautiful and durable metal shell, Use a handle to lift up and down, precise and fast positioning, high reliability.
- ◆ The electrical part of the whole machine has been carefully designed, with high reliability, precision, stability, and ease of use.
- ◆ ARM chip processor, with faster data processing speed.
- ◆ High precision linear calibration before leaving the factory, capable of interpolating multiple points to ensure higher measurement accuracy.
- ◆ Measure the sample viscosity by stepless speed, convenient for operators to choose different shear rates based on the actual application conditions of the sample.
- ◆ The instrument automatically alarms when the measurement exceeds the range.



One-stop PURCHASE

Perfect price-performance ratio products

Professional SERVICE

- ◆ The instrument automatically alarms when the measurement exceeds the range.
- ◆ High speed data transmission interface ensures a fast and stable communication connection between the instrument and the computer.
- ◆ Data storage and exporting data by an external USB function.
- ◆ Built in high-precision PT100 temperature sensor, with high temperature control accuracy and good stability.
- ◆ With calibration function to temperature, ensures precise and reliable temperature for controlling.
- ◆ Powerful and simple calibration function: Users only need one bottle of standard oil and can quickly calibrate the instrument through its built-in calibration menu.
- ◆ Can choose the data collection and programmed analysis software to analyze the rheological features of the sample thoroughly.

Main Technical Parameters:

- ★ Adjustable Speed Range: 5rpm ~ 1000rpm (continuously viable, @1rpm)
- ★ Measurement error: < 2% of full scale
- ★ Sample Volume: < 2ml (See the table below for details)
- ★ Two built-in temperature control for option: 5°C–75°C (L type / Low temperature) ;
50°C–235°C (H type / High temperature)
- ★ Temperature resolution: 0.1°C
- ★ Temperature control accuracy: ± 0.5°C (L type) ; ± 1°C (H type and the set temperature is less than 150°C) or ± 2°C
(H type and the set temperature is higher than 150°C)
- ★ Rotors: 10 types for option (corresponding shear rates and measurement ranges are shown in the table below)
- ★ Power Supply: AC 220V, 50Hz/60Hz, the max. current is about 1.5A
- ★ Size: 275mm × 210mm × 460mm (L × W × H)
- ★ Net weight: 12KG
- ★ Ordering information: BGD 182/1---Low torque Cone-and-plate Viscometer;
BGD 182/2---High torque Cone-and-plate Viscometer

Spindle type	CAP-01	CAP-02	CAP-03	CAP-04	CAP-05	CAP-06	CAP-07	CAP-08	CAP-09	CAP-10
Sample size	67μL	38μL	24μL	134μL	67μL	30μL	1,700μL	400μL	100μL	170μL
Shear rate range (S ⁻¹)	66.5~13,300	66.5~13,300	66.5~13,300	16.5~3,300	16.5~3,300	16.5~3,300	13~2,000	13~2,000	13~2,000	25~5,000
BGD 182/1 Measurement range (mPa.s)	20~1,600	20~3,200	20~6,600	20~13,000	20~26,000	20~66,000	20~2,600	20~10,800	20~44,000	20~4,400
BGD 182/2 Measurement range (mPa.s)	20~37,500	40~75,000	80~150,000	100~300,000	300~600,000	800~1,500,000	78~62,500	313~250,000	125~1,000,000	100~100,000

Note: Calculating the shearrate: 13.33 × the current speed (For CAP-01 toCAP-03) ;
3.33 × the current speed (For CAP-04 toCAP-06) ;
2 × the current speed (For CAP-07 toCAP-09) ;
5 × the current speed (For CAP-10)